

## TECHNICAL DATA SHEET


PRODUCT	<b>HYDROSTATIC TEST EQUIPMENT</b>
MODEL	<b>D2-219REX</b>
SERIES	<b>SERIE D2-10REX</b>



Pneumatic operation dual pump designed for all purpose: Low, medium and high pressure with additional speedy fill-up pump that will help to suction liquids quickly from any container, reservoir, tank or any other thus filling the surface up to 150 psi before active the main pressure pump. Used to check leaks and pressure in boilers, sprinkler systems, pipes, subsea parts, pressure vessels, pressure resistance on testing with water or hydraulic and many other solubles. Most using in oil & gas industries, plants, refineries and oil rigs.

### FEATURES/BENEFITS

- Designed for easy maintenance
- Made with USA highest quality components/solid rubber tires
- All tubing and fittings are stainless steel 316
- Ports: Air supply 3/8 FNPT, liquid inlet 1/2" NPT, discharge 1/2" FNPT
- Unit weight: 150 pounds    Dimensions: 28" x 48" x 18"    Shipping weight: 200lb (70 Kg)



### SPECIFICATIONS

### FILL-UP PUMP

Output Flow	2.40 GPM (9 LPM)	Output Flow	12 GPM (45 LPM)
Max Output Pressure	2100 psi (145 bar)	Max Output Pressure	150 psi (10.5 bar)
Air Supply	100 Psi	Air Supply	60-100 Psi
Inlet	1/2 female NPT	Inlet	1/2 female NPT
Outlet	3/8 female NPT	Outlet	1/2 female NPT
Pump	SC-Hydraulic Ratio 20:1	Pump	Roughneck Double Diaphragm

### PRESSURE GAUGES CALIBRATION & FUTURE MAINTENANCE

- Pressure gauges calibration & chart recorders by customer request
- Maintenance parts or future repairs, all components and accessories can be found on our website [www.hydrorex.com](http://www.hydrorex.com)