


## INDUSTRIAL GAS BOOSTER | PROFESSIONAL

MODEL	<b>Model GB-30-REX</b>
SERIES	<p><b>GB-Series</b></p> <p><b>Single Stage - Single Acting</b></p> <p>The most economical and is ideal for applications not requiring much volume.  <b>Nitrogen, Oxygen, Argon, Helium, Hydrogen and more.</b></p>



### PERFORMANCE CHART



COMFORTABLE		MAX. RATED OPERATIONAL	
Output Pressure	2700 (186 bar)	Max. Output Pressure	4500 (310 bar)
Gas Input	100 - 1300 Psi	Max. Gas Input	1300 - 4500 Psi
Volume Per Stroke	3.1 in <sup>3</sup>	Volume Per Stroke	3.1 in <sup>3</sup>
Flow	100 - 400 LPM	Flow	400 LPM
Air Operate	60 - 90 psi (6 bar)	Air Operate	100 - 120 psi (7 bar)
Max. Air Consumption	72-scfm		

Refer to gas booster performance curve for operating pressures

### CONSTRUCTION & GASES

Variety Gases	Nitrogen, Oxygen, Argon, Helium, Hydrogen and more.
Pump Brand	SC-Hydraulic Engineering
Made In	USA
Components	Parker, McDaniel, Spir Star & Swagelok
Frame	Steel painted frame (Painted Blue) + Stainless steel Control Panel
Dimensions & Weight	22" L x 17" H x 13"W - 90 lbs

### FEATURES

- Infinitely variable output pressure and flow
- Will hold static pressure without generating heat or consuming power
- Standard models are suitable for various gases
- Well proven and trouble-free operation
- Designed for ease of maintenance
- Low cost servicing
- Robust construction

### CONNECTIONS

Gas Inlet	1/4" NPT Female
Gas Outlet	1/4" NPT Female
Air Inlet	3/8" NPT Female
Pressure Hoses	5000 Psi - 3/8" JIC Swivel Nuts - 20ft

### PUMP ON MODEL GB-REX - DRAWING

