



ECONOMIC, DURABLE, SAFE & EASY TO OPERATE

- 13360 Telge Rd. Cypress TX 77429
- sales@hydrorex.com
- Office: 832.277.1182



TECHNICAL DATA SHEET


PRODUCT	HAND & AIR OPERATED PUMP
MODEL	CSS-20000REX
SERIES	SERIE CSS-REX



Compatible with all hydraulic fluids, water, distilled and di-ionized water, solvents, mild chemicals, glycol, liquefied CO2 and many more. Requires 60-100 psi air drive pressure to operate, the CSS series pump is self priming for immediate operation. Hand pump attachment allows for manual operation when shop air is not available or for precision pressure control. Hydrostatic, Burst, Booster, Calibration, Leak Detector and more.

FEATURES/BENEFITS

- Designed for easy maintenance
- 2 gallons (8 liters) - Stainless steel liquid reservoir
- Made in USA components, 4" SS 316 pressure gauge (Quartz USA)
- All tubing and fittings are stainless steel 316
- Ports: Air supply 1/4" FNPT, Outlet pressure 1/4" FNPT.
- Unit weight: 45 pounds Dimensions: 21"L x 16"W x 11"H



SPECIFICATIONS

Output Flow	.07 GPM (0.20 LPM)
Max Output Pressure	20000 psi (1378 Bar)
Air Supply	15-100 Psi
Liquid Tank	2 Gallons / 8 Liters
Outlet	1/4" female MP
Pump	SC-Hydraulic Ratio 195:1

GENERAL PRODUCT INFORMATION

- When operating from 0 to rated hydraulic pressure, air consumption will be approximately 8-16 scfm of free air at 100 psi output. At lower air pressures and higher hydraulic pressures air consumption will be reduced proportionately to flow rates indicated.
- The CSS-REX Series "Dry Lube" pump does not require an air line lubricator.
- Contact Hydrorex for pressure gauges calibration / certificate.
- Maintenance parts for future repairs, all components and accessories can be found on our website www.hydrorex.com

