

TECHNICAL DATA SHEET

PRODUCT	HYDRO PRESSURE WITH DIGITAL CHART RECORDER
MODEL	SP-28000REX
SERIES	SP-REX



Pressure System with Digital Chart Recorder with a 0.15% accuracy in multiple pressure ranges with customizable test reports in a lightweight yet rugged mobile weatherproof case. Easy Software Interface for Real-Time Pressure, Temperature Monitoring, Reporting and record pressure. Light Weight Design (65 lbs.)

SPECIFICATIONS

<u>Model SP-28000REX</u>	<u>Accuracy</u>	<u>Pressure:</u>
Test pressure 28000 Psi	28000 Psi	- 0.15%
Test pressure 1930 Bar	25000 Psi	- 0.18%
Temperature ranges: F or C	20000 Psi	- 0.23%
110 V Electrical power Inlet	10000 Psi	- 0.45%
Output Port 1/4" FHP	5000 Psi	- 0.90%

FEATURES/BENEFITS

- Up to 5Hz – 5 Readings per Second
- Rugged MILSPEC Windows 10 Tablet – 120F Max Working Temp
- Pressure Sensor - Accuracy (NLHR) $\pm 0.15\%$ of span BFSL
- Installed into a Rugged Mobile Case
- USB Plug for easy device connection
- 110 Volt Female Connection for Standard Shop Power
- Recording Software & WORD License Included
- Create customized test certificate
- Automatic temperature compensation

OPTIONAL

- Multiple pressure inlets/sensors for best accuracy pressure
- Upgraded table features
- External display adapters.

TECHNICAL DATA SHEET


PRODUCT	HYDROSTATIC TEST EQUIPMENT
MODEL	284REX
SERIES	10-5 REX



Pneumatic operation, lightweight portable, compact, economic, safe, durable and easy to operate; made in USA with highest quality components for low operational cost. This equipment is available for use on a wide range of fluids including water, oil/hydraulic, glycol and other solubles used in most industries including Oil & Gas.

FEATURES/BENEFITS

- Designed for easy maintenance
- Air operated liquid pump
- All pressure valves, tubing, fittings & hardware are stainless 316
- Ports: Air supply 1/4" FNPT, liquid inlet 3/8" FNPT,
- Output pressure 1/4" FHP, bleed/release 1/4" FNPT
- Steel frame, Unit weight: 65 pounds - Dimensions: 25"x20"x14"



SPECIFICATIONS

Output Flow	0.18 GPM (0.70 LPM)
Max Output Pressure	28000psi (1930) bar
Air Supply	100 Psi
Inlet	3/8" female NPT
Outlet	1/4" female HP
Pump	SC-Hydraulic Ratio 280:1

GENERAL PRODUCT INFORMATION

- When operating from 0 to rated hydraulic pressure, air consumption will be approximately 16-28 scfm of free air at 100 psi output. At lower air pressures and higher hydraulic pressures air consumption will be reduced proportionately to flow rates indicated.
- The 20REX Series "Dry Lube" pump does not require an air line lubricator.
- Contact Hydrex for pressure gauges calibration / certificate.
- Maintenance parts for future repairs, all components and accessories can be found on our website www.hydrex.com