



ID8 - Series: A

Hose Type M-3/8

Hydrostatic Hose 0-10,000 Psi

Applications:

Hydrostatic:

Pressure test, booster, burst test, injection, hydro, function test, static pressure. Pressure test equipment Bolt tensioning, (valves, tooling, instrumentation, panels, controls, jacks) hydroforming, subsea, hydraulics and more.

Liquids & Gasse

Hydraulics, Waters, Oils, Glycol (Nitrogen, Oxygen, Helium, Hydrogen, Air, Argon)

Technical Information

Inner Core:

Polyamide (PA)

Pressure Support:

2 layers of high-tensile steel wire

Polyamide (PA)

Outer Cover:


Yellow


Color: Temperature:

-30°C to +60°C [-22°F to 140°F]



Ø ID	Ø OD	Working Pressure -- (SF 2,5:1)	Burst Pressure	Bend Radius	Weight	Insert ID
8.1 mm	13,3 mm	--	690 bar	1.725 bar	130 mm	0,200 kg/m
0,32 inch	0,52 inch	--	10.005 psi	25.010 psi	5,12inch	0,134lbs/ft

Part no.	Thread	Material	Dimensions (mm)				Sleeve
			A	B	C	⌀	
Sleeve							
11320101	-	Steel	19	44	-	-	

Part no.	Thread	Material	Nut	Dimensions (mm)				Insert
				A	B	C	⌀	
Male fitting								
31320401A	3/8 x 18 NPT	Steel	-	8,5	90	18	22	
31320405A	3/8 x 18 FAISI			8,5	90	18	22	
	316Ti-3/8" Male NPT							

Hose Quick Disconnect



Order with 2 quick disconnect sets

0-15,000 Psi pressure hoses quick disconnects (all stainless steel) coupler and nipple set 3/8" female NPT

Part# CQD-06-SET

www.hydrorex.com

