



ID13 - Series: A

Hose Type 13/2 Hydrostatic Hose 0-10,000 Psi

Applications:

Hydrostatic:

Pressure test, booster, burst test, injection, hydro, function test, static pressure. Pressure test equipment Bolt tensioning, (valves, tooling, instrumentation, panels, controls, jacks) hydroforming, subsea, hydraulics and more.

Liquids & Gasse

Hydraulics, Waters, Oils, Glycol (Nitrogen, Oxigen, Helium, Hydrogen, Air, Argon)

Technical Information

Inner Core:

Polyamide (PA)

Pressure Support:

2 open layers, 2 dense layers of high-tensile steel wire
Polyurethane (TPU)

Outer Cover:


Black

Color: Temperature:

-30°C to +60°C [-22°F to 140°F]



Ø ID	Ø OD	Working Pressure -- (SF 2,5:1)	Burst Pressure	Bend Radius	Weight	Insert ID
12,9 mm	19,3 mm	--	690 bar	1.725 bar	200 mm	0,435 kg/m
0,51 inch	0,76 inch	--	10.005 psi	25.010 psi	7,87 inch	0,291 lbs/ft

Part no.	Thread	Material	Dimensions (mm)				Sleeve
			A	B	C	⌀	
Sleeve							
11320101	-	Steel	26	58	-	-	

Part no.	Thread	Material	Nut	Dimensions (mm)				Insert
				A	B	C	⌀	
Female fitting JIC (swivel nuts)								
VIPER	1/2" JIC Female	Steel	-	4	67	20	19	



Order with 2 JIC adapters Options

0-10,000 Psi pressure hoses male JIC adapters (all stainless steel)

1/2" Male JIC x 1/2" Male NPT (Part# SS-2404-08-08)

