

- 13340 Telge Rd. #401 Cypress TX 77429
- eli@hydrorex.com



• Office: 832.277.1182

TECHNICAL DATA SHEET

PRODUCT	HAND & AIR OPERATE SYSTEM
MODEL	HIP-3500REX
SERIES	SERIE HIP-REX
API	CERTIFIED ACCORDING TO API SPECIFICATIONS



The HIP series pump is self priming for immediate operation. Hand pump attachment allows for manual operation when shop air is not available or for **Precision Pressure Control**. Safe, durabble and easy to operate. Made in USA with highest quality components. Available for use on a wide range of fluids including water, oil/hydraulic and other solubles; **Designed** for Hydrostatic, Calibration, Pressure Certification, Burst, Booster, Hydro, Injection, Leak Detector, and More.

FEATURES/BENEFITS

- Designed for easy maintenance
- Low cost servicing
- Hand operated
- All pressure valves, tubing, fittings & hardware are stainless 316
- Pressure Chart Recorder Port (Optional)
- Stainless frame, Unit weight: 25 pounds Dimensions: 20"L X 12" W 10"H
- HS Code: 8413.50.0050
- Certificated according to API specifications

PERFORMANCE DATA


Output Flow	2.5 LPM
Max Output Pressure	3500 psi (242 Bar)
Operation - Driven	Hand
Flow:	0.14 Cu. in per Cycle
Liquid Inlet Port	3/8" female NPT - Included 3/4" GHT garden Hose adpater
Outlet Pressure Port	1/4" female NPT
Pump Brand & Ration	SC-Hydraulic Ratio 35:1












GENERAL PRODUCT INFORMATION

- When operating from 0 to rated hydraulic pressure, air consumption will be approximately 12 scfm of free air at 100 psi output. At lower air pressures and higher hydraulic pressures air consumption will be reduced proportionately to flow rates indicated.
- The HIP-REX Series "Dry Lube" pump does not require an air line lubricator.
- Contact Hydrorex for pressure gauges calibration / certificate.
- Maintenance parts for future repairs, all components & accessories can be found on our website www.hydrorex.com.











HIP-REX SERIES HIHG PRESSURE HAND PUMP



