



ID8 - Series: A

3/8" NPT Hose Type M-3/8 Hydrostatic Hose 0-10,000 Psi

Applications:

Hydrostatic:

Pressure test, booster, burst test, injection, hydro, function test, static pressure. Pressure test equipment Bolt tensioning, (valves, tooling, instrumentation, panels, controls, jacks) hydroforming, subsea, hydraulics and more.

Liquids & Gasse

Hydraulics, Waters, Oils, Glycol (Nitrogen, Oxygen, Helium, Hydrogen, Air, Argon)

Technical Information

Inner Core:

Polyamide (PA)

Pressure Support:

2 layers of high-tensile steel wire
Polyamide (PA)

Outer Cover:


Yellow


Color: Temperature:

-30°C to +60°C [-22°F to 140°F]



Ø ID	Ø OD	Working Pressure -- (SF 2,5:1)	Burst Pressure	Bend Radius	Weight	Insert ID
8.1 mm	13,3 mm	--	690 bar	1725 mm	0,200 kg/m	5,5 mm
0,32 inch	0,52 inch	--	10.005 psi	25.010 psi	5,12inch	0,134lbs/ft
						0,22 inch

Part no.	Thread	Material	Dimensions (mm)				Sleeve
			A	B	C		
Sleeve							
11320101	-	Steel	19	44	-	-	

Part no.	Thread	Material	Nut	Dimensions (mm)				Insert	
				A	B	C	W		
Male fitting									
H10-10K-6NPT	3/8" NPT			8,5	90	18	22		
H20-10K-6NPT				8,5	90	18	22		
H50-10K-6NPT									
H75-10K-6NPT									
H100-10K-6NPT									

Hose Quick Disconnect

Order with 2 quick disconnect sets

0-15,000 Psi pressure hoses quick disconnects (all stainless steel) coupler and nipple set 3/8" female NPT

Part# CQD-06-SET

www.hydrorex.com

