



Hose Type 1 3/2 Hydrostatci Hose 0-10,000 Psi

1/2 Female JIC (AN) 1322093

ID13 - Series: A

Applications

- Waterblast:** Heat exchanger tube cleaning, surface preparation (concrete removal, surface cleaning of buildings, paint removal)
- Hydraulics:** Pressure test equipment (valves, tooling and control panels)
- Oil and Gas:** Grease injection


Technical Information

- Inner Core:** Polyamide (PA)
- Pressure Support:** 2 layers of high-tensile steel wire
- Outer Cover:** Polyamide (PA)
- Color:** Yellow
- Temperature:** -30°C to +60°C [-22°F to 140°F]




Ø ID	Ø OD	Working Pressure -- (SF 2,5:1)	Burst Pressure	Bend Radius	Weight	Insert ID
12,9 mm	19,3 mm	--	690 bar	1.725 bar	200 mm	0,435 kg/m
0,51 inch	0,76 inch	--	10.005 psi	25.010 psi	7,87 inch	0,291 lbs/ft

Part no.	Thread	Material	Dimensions (mm)				Sleeve
			A	B	C	Ø	
11320101	-	Steel	26	58	-	-	



Part no.	Thread	Material	Nut	Dimensions (mm)				Insert
				A	B	C	Ø	
Female fitting JIC (swivel nuts)								
H10-10K-8JIC	1/2" AN	STAINLESS	-					
H20-10K-8JIC								
H50-10K-8JIC								
H50-10K-8JIC								
H100-10K-8JIC								

Technical drawing of a female fitting JIC (swivel nut) showing dimensions A, B, C, and Ø. The drawing illustrates the internal structure of the fitting, including the swivel nut and the internal threads. Dimension A is the length of the fitting, B is the length of the internal threads, C is the length of the swivel nut, and Ø is the outer diameter of the fitting.



Order with 2 JIC adapters Options

0-10,000 Psi pressure hoses male JIC adapters (all stainless steel)

- 1/2" Male JIC x 3/8" Male NPT (Part# HNMJ8-NM6)
- 1/2" Male JIC x 1/2" Male NPT (Part# HNMJ8-NM8)

