

## Jack Hose/Dixon Hydrostatic Pressure Hose

**Key Note:** 5,000 PSI static pressures, hydraulic lifting jacks, hydrostatic testing

### Jack Hose



- 1- Synthetic Rubber Tube
- 2- Two High Tensile Steel Wire Spirals
- 3- Synthetic Rubber Cover

**Tube:** Oil resistant, synthetic rubber

**Reinforcement:** Two braids of high tensile steel wire



**Cover:** Oil and weather resistant synthetic rubber

**Temperature:** -40° F / +212° F, Intermittent use up to 250° F

**Application:** Hydraulic oil, water

**Termination:** 200 series, bite to wire, 1-piece fitting



Part Number	Hose I.D.	Hose Ends	Max Working Pressure	Minimum Burst Pressure	Length	Conn. NPT
	(in)	Type	(psi)	(psi)	(ft)	
4-NPT	1/4"	1/4" MNPT	5,000	12,000	Custom	
6-NPT	3/8"	3/8" MNPT	5,000	11,000	Custom	
8-NPT	1/2"	1/2" MNPT	5,000	10,000	Custom	
4-JIC	1/4"	1/4" FJIC	5,000	12,000	Custom	Conn. AN (JIC) 
6-JIC	3/8"	3/8" FJIC	5,000	11,000	Custom	
8-JIC	1/2"	1/2" FJIC	5,000	10,000	Custom	

## NPT Hose Order with 2 Screw Type Quick Disconnects (Stainless)



Part Number	Description	Max Working Pressure
CQD-04-SET	1/4" NPT Female & Female Screw Together Quick Disconnect	15,000 psi
CQD-06-SET	3/8" NPT Female & Female Screw Together Quick Disconnect	15,000 psi
CQD-08-SET	1/2" NPT Female & Female Screw Together Quick Disconnect	15,000 psi

## AN (JIC) Hose Order with 2 AN (JIC) to NPT Hose Adapter (Stainless)



SS-4AN-4NPT	1/4" NPT Male X 1/4" JIC Male	8,000 psi
SS-6AN-4NPT	1/4" NPT Female x 3/8" JIC Male	8,000 psi
SS-6AN-6NPT	3/8" NPT Male X 3/8" JIC Male	8,000 psi
SS-6AN-8NPT	1/2" NPT Male x 3/8" JIC Male	8,000 psi
SS-8AN-8NPT	1/2" NPT Male x 1/2" JIC Male	8,000 psi