



ID6 - Series: A

1/4" JIC Hose Type 6/2W Hydrostatic Hose 0- 15,000 Psi

Applications

Hydrostatic:

Pressure test, booster, burst test, injection, hydro, function test, static pressure. Pressure test equipment Bolt tensioning, (valves, tooling, instrumentation, panels, controls, jacks) hydroforming, subsea, hydraulics and more.

Liquids & Gases

Hydraulics, Waters, Oils, Glycol (Nitrogen, Oxygen, Helium, Hydrogen, Air, Argon)

Technical Information

Inner Core:

Polyamide (PA) 2 open layers, 2 dense layers of high-tensile steel wire Polyurethane (TPU)

Pressure Support

Outer Cover:

Color:


Black


Temperature:

-30°C to +60°C [-22°F to 140°F]



Ø ID	Ø OD	Working Pressure -- (SF 2,5:1)	Burst Pressure	Bend Radius	Weight	Insert ID
6,0 mm	12,0 mm	--	1.280 bar	95 mm	0,230 kg/m	4,0 mm
0,24 inch	0,47 inch	--	18.560 psi	3,74 inch	0,154 lbs/ft	0,16 inch

Part no.	Thread	Material	Dimensions (mm)				Sleeve
			A	B	C	Ø	
I0630191W	-	Steel	15,4	43	-	-	
I0630195W	-	AISI 316Ti	15,4	43	-	-	

Part no.	Thread	Material	Nut	Dimensions (mm)				Insert
				A	B	C		
1/4" Female fitting JIC (AN)								
H10-15K-4JIC	1/4" FJIC (AN)	-						
H20-15K-4JIC								
H50-15K-4JIC								
H75-15K-4JIC								
H100-15K-4JIC								

Hose Male JIC to NPT adapters 37 Degree

Order with 2 JIC adapters Options



0-15,000 Psi pressure hoses male JIC adapters
(all stainless steel)

1/4" Male JIC x 1/4" Male NPT (Part# HMJ4-NM4)

1/4" Male JIC x 3/8" Male NPT (Part# HMJ4-NM6)

1/4" Male JIC x 1/2" Male NPT (Part# HMJ4-HM8)

