



ID8 - Series: A

3/8" Female JIC Hose Type 8/2W Hydrostatic Hose 0- 15,000 Psi

Applications

Hydrostatic:

Pressure test, booster, burst test, injection, hydro, function test, static pressure. Pressure test equipment Bolt tensioning, (valves, tooling, instrumentation, panels, controls, jacks) hydroforming, subsea, hydraulics and more.

Liquids & Gases

Hydraulics, Waters, Oils, Glycol (Nitrogen, Oxygen, Helium, Hydrogen, Air, Argon)

Technical Information

Inner Core:

Polyamide (PA) 2 open layers, 2 dense layers of high-tensile steel wire Polyurethane (TPU)

Pressure Support

Outer Cover:

Color:


Black


Temperature:

-30°C to +60°C [-22°F to 140°F]



Ø ID	Ø OD	Working Pressure -- (SF 2,5:1)	Burst Pressure	Bend Radius	Weight	Insert ID
8,0 mm	14,3 mm	--	1.040 bar	110 mm	0,314 kg/m	5,5 mm
0,31 inch	0,56 inch	--	15.080 psi	4,33 inch	0,210 lbs/ft	0,22 inch

Part no.	Thread	Material	Dimensions (mm)				Sleeve
			A	B	C	⌀	
Sleeve							
I0830191W	-	Steel	18,3	43	-	-	
I0830195W	-	AISI 316Ti	18,3	43	-	-	

Part No.	Thread	Material	Nut	Dimensions (mm)				Insert
				A	B	C		
3/8 NPT Male fitting								
H10-15K-6JIC H20-15K-6JIC H50-15K-6JIC H75-15K-6JIC H100-15K-6JIC	3/8" Female JIC	-	-	5,5	68	14	14	

Hose Quick Disconnect

Order with 2 JIC adapters Options



0-15,000 Psi pressure hoses male JIC adapters
(all stainless steel)

3/8" Male JIC x 1/4" Male NPT (Part# HMJ6-NM4)

3/8" Male JIC x 3/8" Male NPT (Part# HMJ6-NM6)

3/8" Male JIC x 1/2" Male NPT (Part# HMJ6-HM8)

