

INDUSTRIAL GAS BOOSTER | PROFESSIONAL

MODEL **Model C-GBD-D75-REX**

SERIES **C-GBD-D-Series**


Double Acting - Double Head

Has the same characteristics of the standard GBD however the double head allows half the input pressure to achieve the same outlet pressure

Nitrogen, Argon, Helium, Hydrogen and more.



PERFORMANCE CHART



COMFORTABLE

MAX. RATED OPERATIONAL

Output Pressure	20,000 (1378 bar)	Max. Output Pressure	25,000 (1723 bar)
Gas Input	250 - 6500Psi	Max. Gas Input	6500 -12000 Psi
Volume Per Stroke	2.4 in ³	Volume Per Stroke	2.4 in ³
Flow	200- 1500 LPM	Flow	1500 LPM
Air Operate	60 - 90 psi (6 bar)	Air Operate	100 - 120 psi (7 bar)
Max. Air Consumption	24-56-scfm		

Refer to gas booster performance curve for operating pressures

CONSTRUCTION & GASES

Variety Gases	Nitrogen, Argon, Helium, Hydrogen and more.
Pump Brand	SC-Hydraulic Engineering
Made In	USA
Components	Parker, McDaniel, Spir Star & Swagelok
Frame	Waterproof Case (Black) + Stainless steel Control Panel
Dimensions & Weight	Shipment Weight: 160 lbs / Dimensions: 32 x 24 x 20

FEATURES

- Infinitely variable output pressure and flow
- Will hold static pressure without generating heat or consuming power
- Standard models are suitable for various gases
- Well proven and trouble-free operation
- Designed for ease of maintenance
- Low cost servicing
- Robust construction

CONNECTIONS

Gas Inlet	3/8" MP Female
Gas Outlet	1/4" HP Female
Air Inlet	1/2" NPT Female
Bleed	1/4" NPT Female

PUMP ON MODEL GB-REX - DRAWING

